

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A61F 13/64</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/21522 (43) International Publication Date: 6 May 1999 (06.05.99)</p>
<p>(21) International Application Number: PCT/SE98/01861 (22) International Filing Date: 16 October 1998 (16.10.98) (30) Priority Data: 9703882-2 24 October 1997 (24.10.97) SE (71) Applicant (for all designated States except US): SCA HYGIENE PRODUCTS AB [SE/SE]; S-405 03 Göteborg (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): CARLBARK, Olle [SE/SE]; Stomvägen 2B, S-428 30 Källered (SE). STRAN-NEMALM, Kenneth [SE/SE]; Brovägen 32, S-448 31 Floda (SE). KÖLBY FALK, Ewa [SE/SE]; Geteryggsgatan 22, S-416 78 Göteborg (SE). (74) Agents: BERG, Sven, Anders et al.; Albihns Patentbyrå Stockholm AB, P.O. Box 5581, S-114 85 Stockholm (SE).</p>		<p>(81) Designated States: AU, BR, JP, KR, MX, NZ, PL, RU, TR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.</p>
<p>(54) Title: A WAIST BELT FOR ABSORBENT GARMENTS</p> <p>(57) Abstract</p> <p>The present invention relates to a garment (1) that includes an absorbent part (2) and a waist belt (3) which is attached directly or indirectly to the garment (1). The belt (3) includes two belt-portions (7, 8) which extend essentially in mutually opposite directions from said absorbent part (2) and which are intended to be fastened together around the wearer of the garment (1). The handling properties and comfort properties of the garment have been greatly improved by using a belt (3) whose stiffness varies in the cross-direction thereof.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A WAIST BELT FOR ABSORBENT GARMENTS

FIELD OF INVENTION

5 The present invention relates to a garment that comprises an absorbent part and a waist belt which is attached directly or indirectly to the garment, wherein the belt has two belt portions that extend in respective opposite directions from said absorbent part and which can be fastened together around
10 the wearer of said garment.

BACKGROUND OF THE INVENTION

Absorbent garments of the aforesaid kind are well known in
15 this field. The garment in question has a belt attached to the absorbent part of the garment and, subsequent to fastening the belt around the wearer's waist with the attached end of the garment located at the rear of the wearer, requires that end of the garment which is not
20 fastened to the belt to be brought between the wearer's thighs and detachably fastened to the front side of the belt with the aid of some type of fastener means. Such releasable fastener means may have the form of hooks and loops (such as touch-and-close fasteners), e.g. fasteners retailed under the
25 designation "VELCRO". An example of one such garment is described in WO-A1-94/26224.

It is also well known within this particular field to use loose belts to which an absorbent unit is fastened, therewith
30 enabling one and the same belt to be used over a longer period of time and together with a number of changes of absorbent units. A loose belt of this kind is intended for use with an absorbent unit illustrated and described in WO-A1-94/26225.

TECHNICAL PROBLEMS

One well known problem with belted garments of the aforesaid
5 kind exists in the handling of those parts of the belt that
protrude out from each side of the absorbent part of the
combined garment, so as to enable the belt-portions to be
gripped quickly and correctly and then fastened together.
With respect in particular to incontinence problems, it will
10 be understood that persons suffering from incontinence are
often old and physically handicapped in some way or another.
Consequently, there is need of a solution which will enable
the absorbent garment to be correctly positioned on the
wearer in a simple fashion.

15 A solution to this problem is taught by WO-A1-94/26222,
according to which the belt is given a degree of stiffness
such as to prevent excessive wrinkling of the belt and
therewith facilitate handling of said belt.

20 Another aspect of the use of a stiff or rigid belt is
described in UK Patent Specification GB-A-2,216,774, where a
portion of the waist part, which can be interpreted as a
belt-portion, comprises a stiffening element. It is said that
25 this stiffening element functions to reduce wrinkling in this
region, therewith reducing the risk of leakage.

It is thus desirable from several aspects to use a belt which
has a relatively high stiffness. Unfortunately, however, a
30 very stiff belt is liable to cause discomfort to the wearer
in use, for instance is liable to cut into and chafe the
wearer's skin. In addition, a stiff belt has relatively
little pliability and will not therefore adapt readily to the
shape of the wearer's body. This problem is particularly
35 significant in the case of broad belts, which are
consequently often felt particularly uncomfortable to wear.

There is thus also a need of a solution which will allow the use of a relatively stiff, or rigid, belt, that is comfortable to wear and that will not increase the danger of the belt cutting into and chafing the wearer's skin.

SUMMARY OF THE INVENTION

The aforesaid problems are avoided essentially completely with the present invention. Thus, an object of the present invention is to provide a belt with which the risk of chafing the wearer's skin and causing other forms of skin irritation is markedly reduced. An inventive belt is primarily characterised in that it has a stiffness which varies in the cross-direction of the belt.

By configuring the belt with a stiffness which is greater in a longitudinally extending central part of the belt than in at least one longitudinally extending edge-part of said belt, there is provided a belt whose stiffness is sufficient to avoid the aforesaid handling and leakage problems while, at the same time, providing a soft belt edge which is comfortable to the user. Because the edge of the belt has a low degree of stiffness, it can be adapted to the shape of the wearer's body without impairing wearer comfort.

A belt comprising an essentially homogenous material is given the desired properties, for instance, by making the cross-sectional area smaller at the edge-parts of the belt than at the central part thereof. A belt of this design is particularly beneficial when the cross-sectional area decreases continuously from the longitudinally extending centre line of the belt towards the longitudinal edges of said belt.

Other preferred characteristic features of the invention and further embodiments thereof will be apparent from the following dependent claims.

5 BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described in more detail with reference to the accompanying drawings, in which

10 Fig. 1 illustrates a garment which comprises a belt constructed in accordance with the invention;

Fig. 2 is a cross-sectional view of the belt shown in Fig. 1;

15 Fig. 3 illustrates another embodiment of an inventive belt;

Fig. 4 is a cross-sectional view of the belt shown in Fig. 3; and

20 Fig. 5 illustrates a third embodiment of an inventive belt.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Fig. 1 shows a garment generally referenced 1. The garment
25 comprises an absorbent part 2 and a belt-portion, generally referenced 3. The belt may be a full belt 3 which is fastened to the absorbent part at its one end 4 (or 5). Alternatively, the belt 3 may comprise two mutually separate parts disposed on respective sides of the absorbent part 2 at one end 4 of
30 said absorbent part. The illustrated belt has a longitudinal direction L and a cross-direction T. The manner in which the belt is fastened is not significant to the present field of use. Thus, the belt 3 may be fastened permanently to the absorbent part 2, i.e. glued, welded, sewn thereto or
35 fastened thereto in some other way. Releasable fastener

devices may also be used, such as buttons, press-studs, clips, touch-and-close fasteners, or corresponding means.

5 If it is desired to incorporate suppleness and resilience in a belt that includes two mutually separate parts, it is conceivable for one end 4 (or 5) of the absorbent part of the garment to be made elastic.

10 The general appearance of the illustrated garment is known to the art and consequently not all of the component parts of said garment will be described in detail in this document. The belt 3 comprises a first belt-portion 7 that projects out from one first side-edge 41 of the absorbent part 2, and a
15 second belt-portion 8 that projects out from the opposing side-edge 42 of said absorbent part. A fastener device 6 in the form of a surface that presents hooked elements and forming part of a touch-and-close fastener means is provided on one end portion of the first belt-portion 7. The fastener
20 device 6 may either be fastened to the other belt-portion 8 (on the side thereof not shown in Fig. 1) or to a receiving area that includes loop-elements and arranged on the second belt-portion 8. The fastener device 6 may alternatively consist of an adhesive material which is either fastened to
25 the second belt-portion 8 (on the side thereof not shown in Fig. 1) or to a specially designed receiving surface against which the adhesive fastener device 6 can be fastened and released repeatedly.

30 As is made apparent hereinafter, further advantages are afforded by special dimensions and designs of the belt 3. Although the belt is preferably generally oblong in shape, it may, of course, have other elongated shapes. However, when the belt has an oblong shape its width will preferably lie
35 between 70 mm and 160 mm so as to enable the belt to be used by adults that are incontinent.

When using an inventive belt, the belt-portions 7 and 8 can be given good handling properties by choosing a belt material that is sufficiently stiff to avoid wrinkling problems while, nevertheless, avoiding problems associated with reduced
5 wearer comfort, such as chafing of and biting into the wearer's skin.

A nonwoven material is preferably used for either one side or both sides of the belt, said nonwoven material preferably
10 being of the kind to which hooked elements on the fastener device 6 can be releasably fastened. The use of nonwoven material as a receiving surface to which the fastener device 6 can be releasably fastened enables particularly beneficial combinations of peeling forces and shear strengths to be
15 obtained. The use of nonwoven material is also beneficial by virtue of the fact that it is less expensive than woven material and thus more appropriate for use with disposable garments.

20 Since wearer comfort is a particularly important factor to which attention must be paid within this field, and then particularly with regard to belt stiffness, it has been found advantageous to construct the belt in accordance with the present invention. As before mentioned, the belt will
25 beneficially have a certain degree of stiffness, particularly in its longitudinal direction L. At the same time, the risk of the belt edges cutting into the wearer's skin or chafing the wearer's skin is greater in the case of a stiff belt than in the case of a belt which is softer and more pliable. With
30 the intention of addressing this risk, the inventive belt is constructed so that its stiffness will vary in the cross-direction T of the belt, thereby enabling the belt to conform to the shape of the wearer's body in use much more readily than might otherwise be the case.

Fig. 2 is a cross-sectional view of the belt 3 shown in Fig. 1. As will be apparent, the belt, which has a generally homogenous construction, comprises a central part 18 that is of predetermined stiffness. Because the belt has been constructed so that the cross-sectional area of said belt decreases in a direction towards the edge-parts 16 and 17 thereof, the stiffness of the belt will also decrease continuously in said edge-parts 16, 17. These parts 16 and 17 can thus conform to the wearer in use, for instance bulge out when necessary, therewith reducing the risk of chafing and of the belt cutting into the wearer's skin and also reducing the risk of impaired user comfort.

Fig. 3 illustrates another embodiment of the present invention in which the belt 3 comprises in its cross-direction T a plurality of mutually adjacent regions 9, 10, 11, 12, 13, 14 and 15 of mutually different stiffness, the extensions of these regions in the longitudinal direction L coinciding essentially with the length of the belt 3. These regions are preferably disposed so that the central part of the belt will be stiffer than the edge-parts of said belt. It is also conceivable for the belt to be constructed so that only one edge-part will have this greater pliability, preferably that edge-part which lies uppermost in use. Neither is it necessary for the regions 9, 10, 11, 12, 13, 14 and 15 to extend through the full thickness of the belt. For instance, these regions may be disposed on a layer 20 that is preferably placed proximal to the wearer's body in use.

Fig. 4 is a cross-sectional view of the belt 3 shown in Fig. 3 provided with a layer 20 which by virtue of its holding effect on said regions 9-15 facilitates manufacture of the belt, in addition to enhancing wearer comfort.

Fig. 5 illustrates a third embodiment of a continuous belt constructed in accordance with the present invention. The

belt 3 of the Fig. 5 embodiment includes a plurality of mutually adjacent regions 29, 30, 31, 32, 33, 34, 35 of mutually different stiffness in the cross-direction T of the belt, said regions being disposed on a first and a second belt-portion 7, 8. A part M of the belt 3 located centrally between the two stiffened belt-portions 7, 8 as seen in the longitudinal direction of the belt 3 includes no stiffening material and thus has one and the same degree of stiffness throughout the whole of its area. Thus, those portions 7, 8 of the belt that include regions of mutually different stiffness have an extension in the longitudinal direction L which is shorter than the length of the belt 3. In this case, said regions are placed so as to essentially coincide with the wearer's need for soft edge-parts on the belt 3.

In certain applications, it may be sufficient for the belt to have two longitudinally extending regions of mutually different stiffness. Furthermore, it may be appropriate to leave a piece of each end of the belt free from stiffening material, for instance when the belt is fastened together with the aid of a button/buttonhole fastener. This would facilitate buttoning of the belt. It is therefore not necessary for the belt to have regions of different stiffness along the whole of its length.

One method of achieving the desired difference in stiffness between different parts of the belt in its cross-direction is to treat the edge-parts of the belt in a manner to change the internal structure of the material. According to one embodiment of the invention (not shown), the edge-parts of the belt are softened by heat-treating said parts. According to another embodiment (also not shown) edge-parts of the belt are softened by exposing said edges to radiation, whereas said softening effect is achieved in accordance with another embodiment (not shown) by mechanically working said edge-parts.

Naturally, combinations of the aforesaid methods can be used to produce the desired material properties within the scope of the invention.

5

The invention shall not therefore be considered limited to the aforescribed exemplifying embodiments thereof, since other embodiments are conceivable within the scope of the following Claims.

CLAIMS

1. A garment (1) comprising an absorbent part (2) and a waist belt (3) which has a longitudinal direction (L) and a cross-direction (T) and which is attached directly or indirectly to said garment (1), wherein said belt (3) includes two belt-portions (7, 8) which extend generally in said longitudinal direction (L) in respective directions from said absorbent part (2) and which are intended to be fastened together around a wearer of the garment (1), characterised in that the belt (3) has a stiffness that varies in the cross-direction (T) of the belt (3).
2. A garment according to Claim 1, characterised in that the belt (3) comprises in its cross-direction (T) at least two mutually adjacent regions (9, 10, 11, 12, 13, 14, 15) of mutually different stiffness.
3. A garment according to Claim 2, characterised in that the belt (3) has a longitudinally extending central part that is stiffer than at least one longitudinally extending edge-part of said belt (3).
4. A garment according to Claim 2 or 3, characterised in that the mutually opposing regions (9-15) disposed in the cross-direction of the belt have an extension in the longitudinal direction (L) that essentially coincides with the length of the belt (3).
5. A garment according to Claim 3, characterised in that the regions (29-35) of mutually different stiffness that lie adjacent one another in the cross-direction (T) of the belt have extensions in the longitudinal direction (L) that are shorter than the length of the belt (3).

6. A garment according to any one of the preceding Claims, characterised in that the two belt-portions (7, 8) of said belt (3) are comprised of a generally homogenous material; and in that a cross-section through one or both of said belt-
5 portions (7, 8) presents at least one edge-part that is thinner than the central part of said cross-section.

7. A garment according to any one of the preceding Claims, characterised in that at least one edge-part of the belt (3)
10 has been treated so as to change the stiffness of the material locally.

8. A garment according to Claim 7, characterised in that the edge-part of said belt (3) has been heat-treated.
15

9. A garment according to Claim 7, characterised in that the edge-part of said belt (3) has been treated with electromagnetic radiation.

20 10. A garment according to Claim 7, characterised in that the edge-part of said belt (3) has been worked mechanically.

1/3




FIG.1

2/3




FIG. 2




FIG. 3

3/3




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/01861

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61F 13/64

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3587580 A (JOHN LESLIE JONES, SR), 28 June 1971 (28.06.71), figure 1	1,2
A	figures 1,2	3,5
	--	
A	EP 0528282 A2 (KIMBERLY-CLARK CORPORATION), 24 February 1993 (24.02.93)	1
	--	
A	US 1440 H (NEW ET AL), 2 May 1995 (02.05.95), abstract	1
	--	
A	WO 9426222 A1 (MÖLNLYCKE AB), 24 November 1994 (24.11.94)	1
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

1 February 1999

Date of mailing of the international search report

08-02-1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Leif Törn

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/01861

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9733547 A1 (SCA MÖLNLYCKE AB), 18 Sept 1997 (18.09.97) -- -----	1

INTERNATIONAL SEARCH REPORT
Information on patent family members

21/12/98

International application No.
PCT/SE 98/01861

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	3587580	A	28/06/71	NONE	
EP	0528282	A2	24/02/93	AU 2086592 A	11/02/93
				CA 2053106 A	09/02/93
				JP 5184623 A	27/07/93
				MX 9204018 A	30/06/94
US	1440	H	02/05/95	NONE	
WO	9426222	A1	24/11/94	AT 159419 T	15/11/97
				AU 676734 B	20/03/97
				AU 6763694 A	12/12/94
				CA 2162049 A	24/11/94
				CZ 284432 B	11/11/98
				CZ 9502947 A	14/02/96
				DE 69406443 D,T	19/03/98
				DK 699066 T	25/05/98
				EP 0699066 A,B	06/03/96
				SE 0699066 T3	
				ES 2110238 T	01/02/98
				FI 955442 A	10/11/95
				GB 2277867 A,B	16/11/94
				GB 9409284 D	00/00/00
				GR 3025615 T	31/03/98
				HU 73723 A	30/09/96
				HU 9503058 D	00/00/00
				JP 8510145 T	29/10/96
				NO 954515 A	02/01/96
				NZ 266236 A	20/12/96
				PL 311574 A	19/02/96
				SE 508028 C	10/08/98
				SE 9301630 A	13/11/94
				SK 141495 A	03/04/96
				ZA 9403175 A	11/01/95
WO	9733547	A1	18/09/97	AU 6538996 A	26/02/97
				EP 0840954 A	13/05/98
				SE 504624 C	17/03/97
				SE 9600965 A	17/03/97